

## PRODUCT SPECIFICATIONS



### MAIN UNIT

<b>System Type:</b>	Color Digital Multifunction Imaging System
<b>Functions</b>	
Standard:	Copy, Scan, Print
<b>Operator Panel:</b>	PRISMAsync 15" LCD
<b>Standard Configuration:</b>	imageRUNNER ADVANCE C9075S PRO/ C9065S PRO Main Unit, Duplex Color Image Reader Unit-A1, PRISMAsync iR-ADV C9000S PRO, Operator Panel, Scanning-B1,* Scheduler-A1,* Multiple Queues/Hot Folders-A1,* E-shredding-B1,* X-Rite Eye-One Spectrophotometer
<b>Memory</b>	
Standard/Maximum:	2.5GB RAM
<b>Hard Disk Drive</b>	
Standard:	80GB
Maximum:	1TB
<b>Network Interface Connection</b>	
Standard:	Ethernet (10Base-T/100Base-TX/1000Base-T)
<b>Other Interface</b>	
Standard:	USB (at Operator Panel)
<b>Copy/Print Speed (BW/Color)</b>	
	<b>C9075S</b> <b>C9065S</b>
Letter:	Up to 75/70 ppm Up to 65/65 ppm
Legal/11" x 17":	Up to 45/42 ppm Up to 39/39 ppm Up to 38/35 ppm Up to 33/33 ppm

<b>Paper Sources (20 lb. Bond)</b>	
Standard:	Dual 1,100-sheet Paper Drawers Dual 550-sheet Cassettes 100-sheet Stack Bypass
Optional:	3,500-sheet Paper Deck-A1, 3,500-POD Deck Lite-A1, or 6,000-sheet Multi-Drawer Paper Deck-A1
Maximum:	9,300 Sheets (with Multi-Drawer Paper Deck option)*
<b>Output Paper Capacity (20 lb. Bond)</b>	
With Copy Tray:	250 Sheets
With Staple or Booklet Finisher:	4,250 Sheets
<b>Output Paper Sizes</b>	
Drawers:	Letter
Cassettes:	13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size [5-1/2" x 7-1/8" to 13" x 19-1/4" (140mm x 182mm to 330mm x 488mm)]
Bypass:	13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size [4" x 5-7/8" to 13" x 19-1/4" (100mm x 148mm to 330mm x 488mm)]
<b>Acceptable Paper Weights</b>	
Drawers/Cassettes:	14 lb. Bond to 80 lb. Cover (52 to 220g/m <sup>2</sup> )
Bypass:	14 lb. Bond to 110 lb. Cover (52 to 300g/m <sup>2</sup> )
<b>Duplexing</b>	
Paper Size:	Standard Automatic Trayless Duplexing (Up to 13" x 19")
Paper Weights:	14 lb. Bond to 80 lb. Cover (52 to 220g/m <sup>2</sup> )

<b>Special Media Support</b>	
Drawers:	Transparency
Cassettes:	Transparency, Tab
Bypass:	Transparency, Tracing, Labels, Coated, Textured, Envelopes

<b>Warm-up Time</b>		<b>C9075S</b>	<b>C9065S</b>
From Power On:	6 Minutes	5 Minutes	
From Sleep Mode:	6 Minutes	5 Minutes	
From Energy Saver Mode:	90 Seconds	90 Seconds	
<b>Power Requirements/Plug</b>			
Main Unit:	208V AC, 60Hz, 15A/NEMA 6-15P		
PRISMAsync:	120V AC, 60Hz, 10-5A/NEMA 5-15P		
<b>Power Consumption (Maximum)</b>			
Main Unit:	2.5kW or Less; Sleep Mode: 1.5W		
PRISMAsync:	181W or Less; Sleep Mode: 117W		
Total:	2.68kW or Less; Sleep Mode: 118.5W		
<b>Dimensions (H x W x D)</b>			
Main Unit:	55-1/10" x 44-1/10" x 36-3/4"*** (1400mm x 1120mm x 932mm)**		
	55-1/10" x 50-1/5" x 36-3/4"**** (1400mm x 1275mm x 932mm)***		
PRISMAsync:	16-1/2" x 7-9/10 x 16-9/10" (420mm x 200mm x 430mm)		
<b>Installation Space (W x D):</b>	50-1/5" x 57-1/10" (1275mm x 1450mm) (when Stack Bypass is extended, Operator Panel is in right-most position, and the Cassette is drawn)		
<b>Weight</b>			
Main Unit:*	Approx. 635 lb. (288kg)		
PRISMAsync:	Approx. 35.3 lb. (16kg)		
Total:*	Approx. 670 lb. (304kg)		
<b>Toner (Estimated Toner Yield @ 5% Coverage)</b>			
Black:	72,000 Images		
Color (C,M,Y):	54,000 Images		



# imageRUNNER ADVANCE C9075S PRO C9065S PRO

## MAIN UNIT (continued)

### Image Reader Unit

**Scan Resolution:** Up to 600 x 600 dpi

**Acceptable Originals (Glass):** Sheet, Book, 3-Dimensional Objects (up to 4.4 lb.)

**Max. Original Size:** Up to 11" x 17"

### Document Feeder

**Scan Method:** Single-Pass Duplexing Automatic Document Feeder

### Acceptable Originals

**Paper Sizes:** 11" x 17", Legal, Letter, Letter-R, Statement, or Statement-R

### Paper Weights

**BW Originals:** 13 lb. Bond to 80 lb. Cover (50 to 220g/m<sup>2</sup>)

**Color Originals:** 17 lb. Bond to 80 lb. Cover (64 to 220g/m<sup>2</sup>)

### Scan Speed (BW/Color; Letter)

**Copy/Scan Simplex:** 45/45 ipm (600 dpi)

**Copy/Scan Duplex:** 44/44 ipm (600 dpi)

### Paper Capacity

(20 lb. Bond): 300 Sheets

### Copy Specifications

#### First-Copy-Out Time (Letter)

**BW:** 15 Seconds  
**Color:** 15 Seconds

**Multiple Copies:** 1 to 9,999

**Color Mode:** Black and White, Color

**Magnification:** 25% - 400% (1% Increments)

### Copy Features

**Original:** 1- or 2-sided, Original type, Size, Background

**Output:** 1- or 2-sided, Binding edge, Media, Cover, Layout, Zoom, Align, Shift, Print delivery, Margin erase, Adjust image, Color/Black & white, Punching,<sup>†</sup> Folding,<sup>†</sup> Binding,<sup>†</sup> Trimming<sup>†</sup>

**Job:** Job name, Number of sets, Destination, Separator sheets, Account ID

### Print Specifications

#### First-Print-Out Time (Letter)

**BW:** 8 Seconds  
**Color:** 8 Seconds

**Type:** External

**Processor:** Intel® Quad Core™ i7

**Operating System:** Windows® XPe® SP3

**Memory:** 4GB

**Hard Disk:** 3 x 3.5" SATA II, 250GB, 7200 RPM

**DVD-ROM:** Standard

**Interface Connections:** 10/100/1000Base-T, TCP/IP (LPR/LPD), 9100 Socket (SMB), Static IP/Auto-IP (DHCP)

**PDL Support:** Adobe® PS3 (3019), PDF 1.7, [Extension Level 3 (for Acrobat® 9)], PDF/X, Optimized PS, Optimized PDF

**Engine Resolution:** 1200 x 1200 dpi

**Print Driver Supported OS:** Windows Vista®, Windows 7 (32-bit and 64-bit), MAC® OS X10.4/10.5/10.6 (32-bit), PPD

**Features:** Waiting/scheduled jobs queues, printed jobs archive; One queue and job management for printing and copying; Streaming (spool-while-RIP-while-print-while-clean-up), unlimited job length at constant print speed via clearing up while printing; Multiple standard and customizable workflow profiles; Media-based operation with PRISMA media catalog; Web-based controller Settings Editor; Professional high-speed color management with Adobe ACE Color Management module and dedicated GPU; Calibration per media family and halftone; Spot color editing including CMYK value definition for spot color tints; Unlimited color pre-set definition for easy and time-saving re-use; Scheduler at operating panel: 8 hours plan-ahead functionality for multiple jobs simultaneously; Workflow automation via LPR queues and PDF/PS Hot Folders

**Fonts:** 136 Type 1 fonts for Roman languages; User import of PS fonts via Settings Editor

**Spot Color Libraries:** HKS K, HKS K3000+, HKS N, HKS N 3000+, PANTONE® Goe un/coated, PANTONE® Solid un/coated

### Scan Specifications

**Standard:** Scan-to-E-mail, Scan-to-FTP, Scan-to-USB

**Option:** Scan-to-PRISMAccess

**Scan Resolution:** Up to 600 dpi

**File Format:** (Single/Multi-page) TIFF, JPEG, PDF

### Security Specifications

**Standard:** E-shredding, HTTPS, Password protection per user role (key operator, system administrator, service technician)

**Optional:** Removable HDD

### Environmental Information

- ENERGY STAR® Qualified
- RoHS Compliant
- WEEE Directive

## OPTIONAL ACCESSORIES

### Paper Supply Options

#### Paper Deck Unit-A1

**Paper Capacity:** 3,500 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]

**No. of Drawers:** 1

**Acceptable Paper Weight:** 14 lb. Bond to 80 lb. Cover (52 to 220g/m<sup>2</sup>)

**Acceptable Paper Type:** Thin, Plain, Heavy, Color, Recycled, Pre-Punched

**Acceptable Paper Size:** Letter

**Power Source:** From Main Unit

**Max. Power Consumption:** 44W

**Dimensions (H x W x D):** 22-1/2" x 12-3/4" x 23" (570mm x 323mm x 583mm)

**Weight:** Approx. 81.6 lb (37kg)

#### POD Deck Lite-A1

**Paper Capacity:** 3,500 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]

**No. of Drawers:** 1

**Acceptable Paper Weight:** 14 lb. Bond to 110 lb. Cover (52 to 300g/m<sup>2</sup>)

**Acceptable Paper Type:** Thin, Plain, Heavy, Color, Recycled, Pre-punched, Transparency, Labels, Bond, Letterhead, Coated, Textured

**Acceptable Paper Size:** 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R

**Power Requirement:** 120-127V AC, 60Hz, 5A

**Max. Power Consumption:** 288W

**Plug:** NEMA 5-15P

**Dimensions (H x W x D):** 22-1/2" x 23-5/8" x 24-1/2" (570mm x 601mm x 621mm)

**Weight:** Approx. 110 lb. (50kg)

#### Multi-Drawer Paper Deck-A1

**Paper Capacity:** 6,000 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]

**No. of Drawers:** 3 (2,000 Sheets each)

**Acceptable Paper Weight:** 14 lb. Bond to 110 lb. Cover (52 to 300g/m<sup>2</sup>)

**Acceptable Paper Type:** Thin, Plain, Heavy, Color, Recycled, Pre-Punched, Transparency, Labels, Tab, Bond, Letterhead, Coated, Textured

**Acceptable Paper Size:** 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Custom Size [5-1/2" x 7-1/8" to 13" x 19-1/4" (140mm x 182mm to 330mm x 488mm)]

**Power Requirement:** 120-127V 60Hz 4A

**Max. Power Consumption:** Approx. 753W

**Plug:** NEMA 5-15P

**Dimensions (H x W x D):** 41" x 37-3/8" x 31-3/8" (1040mm x 950mm x 797mm)



## OPTIONAL ACCESSORIES (continued)

### Output Options

#### Copy Tray-P1

Total Output Capacity:	250 Sheets (20 lb. Bond)
Acceptable Paper Weight:	14 lb. Bond to 110 lb. Cover (52 to 300g/m <sup>2</sup> )
Acceptable Paper Size:	13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size [4" x 5-7/8" to 13" x 19-1/4" (100mm x 148mm to 330mm x 488mm)]
Dimensions (H x W x D):	6-7/8" x 16-1/2" x 15" (175mm x 420mm x 382mm) (when Auxiliary Tray is extended)
Weight:	Approx. 2.9 lb. (1.3kg)

#### Staple Finisher-A1

Number of Trays:	3
Total Output Capacity:	4,250 Sheets (Letter, Statement-R, Executive)
Tray A:	1,500 Sheets (Letter, Statement-R, Executive) 750 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R)
Tray B:	250 Sheets (Letter) 125 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R, Executive)
Tray C:	2,500 Sheets (Letter) 1,250 Sheets (Statement-R, Executive) 750 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R)
Acceptable Paper Weight:	14 lb. Bond to 110 lb. Cover (52 to 300g/m <sup>2</sup> )
Acceptable Paper Type:	Thin, Plain, Heavy, Color, Recycled, Pre-Punched, Transparency, Tracing, Labels, Tab, Bond, Letterhead, Coated, Textured, Envelopes
Acceptable Paper Size:	13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size [4" x 5-7/8" to 13" x 19-1/4" (100mm x 148mm to 330mm x 488mm)]
Staple Positions	
Corner/Double Stapling:	11" x 17", Legal, Letter, Letter-R, Executive
Max. Stapling Capacity:	100 Sheets [20 lb. Bond (80g/m <sup>2</sup> ) (Letter, Executive) 50 Sheets [20 lb. Bond (80g/m <sup>2</sup> ) (11" x 17", Legal, Letter-R)]
Paper Capacity of Staple Mode	
Tray A/C:	1,500 Sheets/100 Sets (Letter, Statement-R, Executive), 750 Sheets/50 Sets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R)
Type of Staple:	Staple-G1 (5,000 x 3)
Power Requirement:	100-240V, 50/60Hz, 2.8A
Max. Power Consumption:	207W
Plug:	NEMA 5-15P
Dimensions (H x W x D):	41" x 25-3/4" (30-3/4"++) x 30-1/8" (1040mm x 654mm (782mm++) x 765mm)
Weight:	Approx. 134 lb. (61kg)

#### Booklet Finisher-A1

Number of Trays:	3
Total Output Capacity:	4,250 Sheets (Letter, Statement-R, Executive)
Tray A:	1,500 Sheets (Letter, Statement-R, Executive) 750 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R)
Tray B:	250 Sheets (Letter) 125 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R, Executive)
Tray C:	2,500 Sheets (Letter) 1,250 Sheets (Statement-R, Executive) 750 Sheets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R)
Acceptable Paper Weight:	14 lb. Bond to 110 lb. Cover (52 to 300g/m <sup>2</sup> )
Acceptable Paper Type:	Thin, Plain, Heavy, Color, Recycled, Pre-Punched, Transparency, Tracing, Labels, Tab, Bond, Letterhead, Coated, Textured, Envelopes
Acceptable Paper Size:	13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size [4" x 5-7/8" to 13" x 19-1/4" (100mm x 148mm to 330mm x 488mm)]
Staple Position	
Corner Stapling:	11" x 17", Legal, Letter, Letter-R, Executive
Double Stapling:	11" x 17", Legal, Letter, Letter-R, Executive
Saddle-Stitch:	13" x 19", 12" x 18", 11" x 17", Legal, Letter-R
Max. Stapling Capacity:	100 Sheets [20 lb. Bond (80g/m <sup>2</sup> ) (Letter, Executive) 50 Sheets [20 lb. Bond (80g/m <sup>2</sup> ) (11" x 17", Legal, Letter-R)]
Paper Capacity of Staple Mode	
Tray A/C:	1,500 Sheets/100 Sets (Letter, Statement-R, Executive), 750 Sheets/50 Sets (13" x 19", 12" x 18", 11" x 17", Legal, Letter-R)
Max. Saddle-Stitch Capacity:	20 Sheets [including one cover page 110 lb. Bond (300g/m <sup>2</sup> )] [20 lb. Bond (80g/m <sup>2</sup> )]
Paper Capacity of Saddle-Stitch Mode:	1 to 5 Sheets/25 Sets, 6 to 10 Sheets/15 Sets, 11 to 16 Sheets/10 Sets, 17 to 20 Sheets/5 Sets
Type of Staple:	Staple-G1 (5,000 x 3) Staple-P1 (5,000 x 2)
Power Requirement:	100-240V 50/60Hz, 2.8A
Power Consumption:	255W
Plug:	NEMA 5-15P
Dimensions (H x W x D):	41" x 30-1/4" (35-1/4"++) x 30-1/8" (1040mm x 767mm (896mm++) x 765mm)
Weight:	Approx. 238 lb. (108kg)

#### Puncher Unit-BF1\*\*

Acceptable Punch Paper Weight:	14 lb. Bond to 140 lb. Index (52 to 256g/m <sup>2</sup> )
Acceptable Punch Paper Type:	Thin, Plain, Heavy, Color, Recycled, Tab, Bond, Letterhead, Coated, Textured
Acceptable Punch Paper Size:	11" x 17", Legal, Letter, Letter-R
Punch Type:	2 Holes (Legal, Letter-R) 3 Holes (11" x 17", Letter)
Distance Between Punch Holes	
2 Holes:	2-3/4" (70mm)
3 Holes:	4-1/4" (108mm)
Punch Waste Tray Capacity:	Approx. 5,000 Sheets (20 lb. Bond)
Power Requirement:	From Finisher
Power Consumption:	Approx. 56W (when in operation)
Dimensions (H x W x D):	Inside the Finisher [15-1/2" x 3-3/4" x 15-1/2" (392mm x 95mm x 392mm)]
Weight:	Approx. 8.2 lb. (3.7kg)

#### Inner Booklet Trimmer-A1\*

Trimming Method:	Face Trim
Trim Thickness:	40 Sheets (2mm to 20mm Trimming Width)
Waste Tray Capacity:	1,500 Sheets of Trimmed Strips [Width 0.78" (20mm), Letter, 20 lb. Bond (80g/m <sup>2</sup> )]
Acceptable Paper Weight:	16 lb. Bond to 110 lb. Cover (60 to 300g/m <sup>2</sup> )
Acceptable Paper Type:	Thin, Plain, Heavy, Recycled, Color, Coated
Output Tray Capacity:	30 Booklets
Power Requirements:	From Finisher
Max. Power Consumption:	51W (when in operation)
Dimensions (H x W x D):	Inside the Finisher [15-7/8" x 9-7/8" x 24-5/8" (403mm x 251mm x 625mm)]
Weight:	Approx. 70.5 lb. (32kg)



# imageRUNNER ADVANCE C9075S PRO C9065S PRO

## OPTIONAL ACCESSORIES (continued)

### Output Options (continued)

#### Professional Puncher-C1/

#### Professional Puncher Integration Unit-B1\*\*

Acceptable Punch Paper Weight

Letter  
(3-hole, 5-hole,  
Velo Bind  
11-hole,  
Plastic Comb  
19-hole, Twin  
Loop 21-hole/  
32-hole, Color  
Coil 44-hole): 20 lb. Bond to 80 lb. Cover  
(75 to 216g/m<sup>2</sup>)

Letter  
(ProClick  
32-hole): 20 lb. Bond to 65 lb. Cover  
(75 to 176g/m<sup>2</sup>)

Acceptable Punch Paper Type: Plain, Heavy, Color, Recycled, Tab, Coated

Acceptable Punch Paper Size: Letter

Punch Pattern Die Sets (optional): Plastic Comb (19-hole)  
Twin Loop (21/32-hole)  
Color Coil (44-hole)  
Velo Bind (11-hole)  
Loose Leaf (3/5-hole)  
ProClick (32-hole)

Punch Waste Tray Capacity: Approx. 25,000 Sheets or more of 20 lb. Bond (80g/m<sup>2</sup>) with 4 holes punched

Power Requirement: 120-127V/5.5A-60Hz

Max. Power Consumption

Professional Puncher-C1: 300W

Professional Puncher Integration Unit-B1: 130W Max.

Plug: NEMA 5-15P

Dimensions (H x W x D)

Professional Puncher-C1: 41" x 12" x 31-1/4"  
(1040mm x 305mm x 792mm)

Professional Puncher Integration Unit-B1: 41" x 9-7/8" x 31-1/4"  
(1040mm x 250mm x 792mm)

Weight

Professional Puncher-C1: Approx. 176 lb. (80kg)

Professional Puncher Integration Unit-B1: Approx. 88.2 lb. (40kg)

#### Document Insertion Unit-H1\*\*

Number of Trays: 2

Acceptable Media: Covers and Inserts

Tray Capacity

Upper: 200 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]

Lower: 200 Sheets [20 lb. Bond (80g/m<sup>2</sup>)]

Acceptable Paper Weight: 14 lb. Bond to 110 lb. Cover  
(52 to 300g/m<sup>2</sup>)

Acceptable Paper Type: Thin, Plain, Heavy, Color, Recycled, Pre-punched, Tab, Bond, Letterhead, Coated, Textured

Acceptable Paper Sizes: 13" x 19", 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Custom Size [7-1/8" x 7-1/8" to 13" x 19-1/4" (140mm x 182mm to 330mm x 488mm)]

Power Requirements: 100-240V/2.8A, 50/60Hz

Max. Power Consumption: 103W

Plug: NEMA 5-15P

Dimensions (H x W x D): 55-3/8" x 13-1/4" x 31-1/4"  
(1407mm x 336mm x 793mm)  
55-3/8" x 29-3/8" x 31-1/4"  
(1407mm x 746mm x 793mm)  
(with Insertion Feeding Tray)

Weight: Approx. 134 lb. (61kg)

#### Paper Folding Unit-G1\*\*

Folding Method: Roller Pressure Folding

Folding Type: Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold

Acceptable Paper Weight: 14 lb. Bond to 28 lb. Bond  
(52 to 105g/m<sup>2</sup>)

Acceptable Paper Type: Thin, Plain, Color, Recycled, Bond

Acceptable Paper Sizes

Accordion

Z-Fold, C-Fold,

Half-Fold: Letter-R

Z-Fold: 11" x 17", Legal, Letter-R

Double

Parallel Fold: Legal, Letter-R

Power Requirements: From Finisher

Max. Power Consumption: 130W

Dimensions (H x W x D): 46-7/8" x 13-1/4" x 31-1/4"  
(1190mm x 336mm x 793mm)

Weight: Approx. 156.5 lb. (71kg)

## OTHER OPTIONAL ACCESSORIES

- Operator Attention Light
- Removable HDD Kit-AB1
- 3.5-inch/1TB HDD-B1
- Key Switch Unit-B1
- ADF Access Handle-A1
- Remote Viewer-B1
- Fontset Simplified Chinese-B1
- Fontset Traditional Chinese-B1
- Fontset Japanese-B1
- Fontset Korean-B1

■ PRISMAsync license accessories.

\* Stack Bypass is not available when Multi-Drawer Paper Deck is installed.

\*\* With Operator Panel in left-most position.

\*\*\* With Operator Panel in right-most position.

◆ Includes ADF, consumables, Operator Panel.

† Requires optional accessories.

†† When the Auxiliary Tray is extended.

††† Puncher Unit-BF1 installs internally with either Staple Finisher-A1 or Booklet Finisher-A1.

▲ Option for Booklet Finisher-A1.

▲▲ Requires Staple Finisher-A1 or Booklet Finisher-A1.

NOTE: Some accessories require additional equipment or may be prerequisites for other options. Some accessories cannot be installed simultaneously. Check with your Canon Authorized Dealer for details.

**Canon**  
image*ANYWARE*

1-800-OK-CANON  
www.usa.canon.com

Canon U.S.A., Inc.  
One Canon Park  
Melville, NY 11747

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Océ is a registered trademark owned by Océ Technologies B.V. PANTONE® and other PANTONE®, LLC trademarks are the property of PANTONE®, LLC, CANON, IMAGERUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Some items may not be available at this time; please check for availability. Specifications and availability subject to change without notice.

© 2013 Canon U.S.A., Inc. All rights reserved.  
Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

