



LASERJET ENTERPRISE P3015N PRINTER

Reliable, high-performance laser printing

- Print Speed:** Black (normal, letter): Up to 42 ppm;
Black (normal, A4): Up to 40 ppm
- Print Resolution:** Up to 600 x 600 dpi
- Standard Connectivity:** 1 Hi-Speed USB 2.0 port, 1 front-panel Host USB 2.0 port, 2 internal Accessory ports (for connecting HP or partner solutions), 1 EIO slot, 1 HP Jetdirect 10/100/1000 Base-TX Ethernet print server
- Recommended Monthly Page Volume:** 1,500 to 5,000
- Duplex Print Options:** Manual (driver support provided)



Count on HP for performance and durability

- Grab prints and get back to work quickly with print speeds up to 42 ppm letter/40 ppm A4 and a fast first page out. Quickly process and share large, complex files, using a 540 MHz processor, up to 640 MB expandable memory and gigabit networking.²
- Quickly process and share large, complex files, using a 540 MHz processor, up to 640 MB expandable memory and gigabit networking. Help prevent unauthorized network admission with 802.1X, which provides device authentication prior to admission.²
- All-in-one Original HP print cartridges with built-in intelligence deliver reliable, consistently outstanding results, page after page, cartridge after cartridge. Get more out of each cartridge with the optional high capacity toner cartridge.³
- Save money and time and reduce your environmental impact. Print high-quality, two-sided documents, and use up to 50 percent less paper using automatic, two-sided printing.¹ This device uses up to 13 percent less energy per page than previous models.

Get peace of mind with advanced security features


- Conveniently connect and house your security card swipe and HP and third-party authentication devices with the hardware integration pocket.¹
- Easily retrieve stored confidential print jobs. Retrieve a list of stored jobs using the "menu" button and enter your PIN using the 10-number key pad on the printer's control panel.¹
- Add a secure hard disk to the printer's open EIO slot. The optional HP High-Performance Secure EIO Hard Disk provides advanced security features to protect sensitive data at rest on HP printers and MFPs--without impacting device performance.³

Gain the flexibility to expand with your business

- Extend your printer's capabilities as your business needs change, using an open EIO slot and two internal accessory ports. Plus, the printer's open memory slot allows you to add memory up to 512 MB, for total memory of up to 640 MB.¹
- Improve your productivity. Get the capacity to do more with a 1600-sheet maximum input capacity.⁴ Add an optional 500-sheet paper tray for better paper handling.³

Easy to use and manage

- Get convenient, walk-up printing, using the front-panel Hi-Speed host USB 2.0 port.⁵ Increase your manageability with a full portfolio of innovative HP Certified Partner solutions that integrate easily into your existing infrastructure.
- Easily setup and manage your print fleet with industry leading, award winning HP Web Jetadmin, and the HP Universal Print Driver. Easily install, configure, monitor, troubleshoot, and manage your printing devices from anywhere on the network.²
- Enjoy easy recycling—cartridges returned via HP Planet Partners are recycled responsibly.⁶



¹For d, dn, n, x printer models only. The HP LaserJet Enterprise P3015d printer includes the features of the HP LaserJet Enterprise P3015 printer, plus automatic two-sided printing, a 10-number key pad, and a hardware integration pocket. The HP LaserJet Enterprise P3015dn printer includes the features of the HP LaserJet Enterprise P3015d printer, plus networking. The HP LaserJet Enterprise P3015x printer includes the features of the HP LaserJet Enterprise P3015dn printer, plus a 500-sheet input tray for a 1,100-sheet total input capacity. ²For dn, n, and x models only. The HP LaserJet Enterprise P3015dn printer includes the features of the HP LaserJet Enterprise P3015d printer, plus networking. The HP LaserJet Enterprise P3015x printer includes the features of the HP LaserJet Enterprise P3015dn printer, plus a 500-sheet input tray for a 1100-sheet total input capacity. ³Not included, please purchase separately. ⁴Base, d, dn and n models have a 600-sheet standard input capacity, and the option to add two 500-sheet trays; x model has an 1100-sheet standard input capacity, plus the option to add a 500-sheet tray. ⁵Supports PDF, PRN, and PS file extensions. ⁶Available in select countries. For more information visit: <http://www.hp.com/recycle>.





LASERJET ENTERPRISE P3015N PRINTER

TECHNICAL SPECIFICATIONS

PRINT TECHNOLOGY	Laser
PRINT SPEED¹	Black (normal, letter): Up to 42 ppm; Black (normal, A4): Up to 40 ppm
FIRST PAGE OUT	As fast as 7.5 seconds from Ready mode (letter)
PRINT RESOLUTION	Black (best): Up to 600 x 600 x 2 dpi (1200 dpi effective output); Black (normal): Up to 600 x 600 dpi
PRINT TECHNOLOGY RESOLUTION	300 dpi, 600 dpi, HP FastRes 1200, HP ProRes 1200
STANDARD PRINTER LANGUAGES	HP PCL 5e, HP PCL 6, HP postscript level 3 emulation, direct PDF (v 1.4) printing
NUMBER OF PRINT CARTRIDGES²	1 (black)
SURESUPPLY SUPPORTED³	Yes
PRINTER MANAGEMENT	HP Web Jetadmin, HP LaserJet Utility, HP Embedded Web Server, HP Easy Printer Care
STANDARD CONNECTIVITY	1 Hi-Speed USB 2.0 port, 1 front-panel Host USB 2.0 port, 2 internal Accessory ports (for connecting HP or partner solutions), 1 EIO slot, 1 HP Jetdirect 10/100/1000 Base-TX Ethernet print server
WIRELESS CAPABILITY	Optional, enabled with purchase of a hardware accessory
NETWORK CAPABILITIES	Via HP Jetdirect 10/100/1000 Base-TX Ethernet embedded print server (standard on some models), Optional HP Jetdirect EIO internal print servers, HP Jetdirect external print servers, or HP 802.11b/g wireless print servers
OPTIONAL CONNECTIVITY	HP Jetdirect EIO internal print servers; HP Jetdirect external print servers; HP 802.11b/g wireless print servers; HP EIO Parallel Port Adaptor
CONTROL PANEL	2.29 x 5.33 cm 4 line LCD display, 3 light-emitting diode (LED) indicator lights (Ready, Data, Attention), buttons (10 numeric keys, Information, Return, Stop/Cancel, OK, Toggle up/down
DISPLAY	2.25-in LCD (text), 4 line display, up to 18 characters per line
RECOMMENDED MEDIA WEIGHT (DUPLEX)	16 to 32 lb
DUTY CYCLE	Up to 100,000 pages
RECOMMENDED MONTHLY PAGE VOLUME	Up to 1,500 to 5,000 pages
MAXIMUM/STANDARD MEMORY	Maximum: 640 MB; Standard: 128 MB
MEMORY SLOTS	1 slot 144-pin DIMM
MEDIA TYPES	Paper (bond, color, letterhead, plain, preprinted, prepunched, recycled, rough), envelopes, labels, cardstock, transparencies, user-defined
MEDIA SIZES SUPPORTED	Letter, legal, executive, 8.5 x 13 in, envelopes
CUSTOM MEDIA SIZES	Multipurpose Tray: 3 x 5 to 8.5 x 14 in; Tray 2 and Optional 500-Sheet Feeder/Tray (3 and 4): 4.1 x 5.8 to 8.5 x 14 in
PAPER HANDLING	Input Capacities: 100-sheet multipurpose tray 1, one 500-sheet input tray 2, Up to 1,600 sheets maximum, Up to 600 sheets standard, Up to 10 envelopes; Output Capacities: 250-sheet output bin, 100-sheet rear output bin, Up to 10 envelopes, Up to 75 sheets transparencies
DUPLEX PRINT OPTIONS	Manual (driver support provided)
HARD DISK CAPACITY	Optional, HP High-Performance Secure EIO Hard Disk (EIO Hard Drive)
PROCESSOR	Type: Motorola Coldfire V5; Speed: 540 MHz
SOFTWARE INCLUDED	EVO Discrete PCL 6 (based on EVO 4.7), Product specific Universal Print Drivers Postscript, static install (based on EVO 4.7)

MINIMUM SYSTEM REQUIREMENTS	PC: Microsoft® Windows® 7, Windows Vista®, XP, Server 2003, 2000 (SP4): 200 MB available hard disk space, CD-ROM drive, USB 2.0 port or IEEE 1284-4 compliant parallel port; Mac: Mac OS X v 10.3.9, 10.4, 10.5, 10.6, 200 MB available hard disk space, CD-ROM drive, USB 2.0 port or IEEE 1284-B compliant parallel port
COMPATIBLE OPERATING SYSTEMS	Microsoft® Windows® 7, Windows Vista®, Windows Vista® x64, Windows XP Home, Windows XP Professional, Windows Server 2003, Windows Server 2008, Windows 2000 (SP4), Mac OS X v 10.3.9, 10.4, 10.5, 10.6, Novell NetWare, Red Hat Linux 7.x or higher, SuSE Linux 8.x or higher, Linux (see http://www.hplip.net)
OPERATING ENVIRONMENT	Storage Humidity: 10 to 90% RH; Operating Humidity Range: 10 to 80% RH; Recommended Humidity Operating Range: 30 to 70% RH; Operating Temperature Range: 15 to 32.5° C; Recommended Operating Temperature Range: 59 to 89° F (15 to 32.5° C); Maximum Operating Temperature Range: 59 to 89° F; Storage Temperature Range: -4 to 104° F (-20 to 40° C)
ACOUSTICS	Acoustic Power Emissions: 6.8 B(A); Acoustic Power Emissions (Ready): Inaudible; Acoustic Pressure Emissions: 54 dB(A); Acoustic Pressure Emissions Bystander (Ready): Inaudible
POWER	Power Requirements: Input voltage 100 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); Power Supply Type: Internal; Power Consumption⁴: 780 watts (active), 8.5 watts (sleep), 14.5 watts (standby), 0.6 watts (off); Typical Electricity Consumption (TEC) Number: 3.267 kWh/Week
PRODUCT DIMENSIONS	W X D X H: 17.6 x 28.7 x 12.4 in (with multipurpose tray extended) (448 x 730 x 316 mm (with multipurpose tray extended)) Maximum: 448 x 730 x 316 mm
PRODUCT WEIGHT	35 lb (15.9 kg)
WHAT'S IN THE BOX	HP LaserJet Enterprise P3015n Printer, power cord, HP LaserJet Black Print Cartridge, full capacity (~ 6,000 pages), software and documentation on CD-ROM, Getting Started Guide, support flyer, Warranty Guide (where applicable)
ACCESSORIES	500-sheet Input Tray/Feeder, CE530A; HP Hardware Integration Pocket Cable, CE981A
REPLACEMENT CARTRIDGES	HP LaserJet Black Print Cartridge, CE255A; HP LaserJet Black Print Cartridge, CE255X
WARRANTY	One-year warranty, return to HP authorized service center
HP CARE PACK SERVICES	HP 3-year Next Business Day Exchange, UP871E; HP 3-year Next Business Day Onsite Service, UP872E; HP Installation Service with Network Setup, UC742E

ADDITIONAL INFORMATION

BUSINESS UNIT	Transaction Laser Products
COUNTRY OF ORIGIN	Product of Vietnam
TARIFF NUMBER	8443321010
MATERIAL TYPE CODE	FERT
PALLET INFORMATION	Dimensions: 47 x 39 x 91 in Weight: 926 lb Layers: 5

FOR MORE INFORMATION VISIT OUR WEBSITE AT WWW.HP.COM

HP LASERJET ENTERPRISE P3015N PRINTER Product Number: CE527A

¹Exact speed varies depending on the system configuration, software application, driver and document complexity. ²Introductory cartridge included; yields ~ 1,000 pages. Replacement cartridge declared yield ~ 2,100 pages based on ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see <http://www.hp.com/go/learnaboutsupplies>. ³HP SureSupply alerts you when your print cartridge is running low and helps you purchase online or locally through HP or a participating retailer. Only available with Original HP supplies; Internet access required. For more information, visit <http://www.hp.com/go/SureSupply>. ⁴Values subject to change. See http://www.hp.com/go/lip1600_regulatory for current information. Power numbers are the highest values measured using all standard voltages

©2010 Hewlett-Packard Development Company, L.P. HP is a registered trademark of the Hewlett Packard Company. All other trademarks are the property of their respective owners. Microsoft and Windows are registered trademarks of Microsoft Corporation. Adobe and Acrobat are trademarks of Adobe Systems Incorporated. This listing of non HP products does not constitute an endorsement by Hewlett Packard Company. The information contained herein is subject to change without notice and is provided "as is" without warranty of any kind. HP shall not be liable for technical or editorial errors or omissions contained herein. **January 2011, Rev. 2**