

Simply a SMARTER Way to Work

MFX-3510



Print

- Up to 37 page-per-minute printing / Standard duplex (two-sided) printing
- Standard PCL 5e / XL printing (Windows, Linux, UNIX, AS/400, SAP and more)
- Optional PostScript 3 printing (Macintosh support, PDF direct printing)
- Standard 500-sheet paper cassette and 100-sheet multipurpose bypass tray



Scan

- 80-sheet automatic document feeder (ADF) enables monochrome scanning at up to 25 images-per minute and color scanning at up to 8 images-per-minute
- Standard scanning to e-mail, PC folder, FTP and USB flash drives (PDF, TIFF, JPEG)
- Scan at up to 600 x 600 dpi



Fax

- Standard fax features include a 33.6 Kbps fax modem, 1,000 location address book, broadcasting, group dialing and confirmation reports
- Integrates with a variety of fax server applications
- Archive outbound fax and e-mail transmissions to create an audit trail of communication
- Send faxes directly from PC applications using the simple PC fax driver



Copy

- Copy documents from the 80-sheet ADF or legal-size platen glass
- Card Copy mode enables users to capture both sides of a card or check-sized document seamlessly
- Automatic mixed original detection can detect letter & legal size documents in the ADF and produce output on the appropriate paper size (if both sizes have been loaded)

BUSINESS-CLASS DOCUMENT SOLUTIONS

muratec



MFX-3510
(600 sheets)



MFX-3510
+ 3510CAS
+ 3510CAB
(1,100 sheets)

Scanning Highlights

- Scan color documents at up to 600 × 600 dpi. Scan documents at up to 25 images-per-minute using the automatic document feeder (ADF).
- Quickly scan documents into file folders on your PC or network.
- Scan documents directly to e-mail addresses. Use the QWERTY keypad to create a custom attachment name (document being scanned) or to add processing instructions to an outbound e-mail.
- Integrated address book can store up to 1,000 contacts, each containing a fax number, e-mail address and group locations. Mixed broadcasting (fax/e-mail) is supported.
- Scan documents directly to a USB flash drive.

Printing Highlights

- Deliver single-sided output at 37 pages-per-minute, or duplex output at 10 pages-per-minute.
- Secure printing suppresses print jobs until a password has been entered on the control panel.
- Standard PCL 5e / XL printing support (Windows, Linux, UNIX, AS/400, SAP and more)
- Optional PostScript3, Direct PDF and barcode printing support (supports UPC/EAN, Interleave 25, Code 39, Code 126, PostNet and more).

Copying Highlights

- Legal-size platen glass captures multipart forms, carbon papers, plastic identification cards and more.
- Card copy mode allows for the seamless copying of two-sided driver's licenses and/or insurance cards.
- 5 second first-copy-out-time (FCOT) and 27 second warm-up time.

Faxing Highlights

- Route inbound fax documents to another fax location, e-mail address or PC folder.
- The optional e-mail gateway feature enables users to send documents from the MFX-3510 through a network fax server.
- Send documents directly from PC applications using the simple PC fax driver.
- System administrators can automatically archive all inbound and outbound communications, including both fax and e-mail transmissions, to create an audit trail of usage.

Additional Highlights

- "My MFP" mode enables each user to access commonly used features on a single screen, regardless of which mode the feature is located in.
- Standard 500-sheet paper cassette (letter/legal). Add (1) 500-sheet paper cassette to increase the total paper capacity to 1,100-sheets.
- 100-sheet multipurpose bypass tray is the perfect solution for printing envelopes, labels and more (20-43 lb)
- The optional 2-bin output tray can physically separate copy, fax or print jobs to create a distribution-ready stack of documents.
- 5-line LCD simplifies user operation and job execution.
- Compact footprint enables the installation of the MFX-3510 on the desktop or within a crowded workspace.

Specifications – MFX-3510

| GENERAL | |
|---|---|
| Configuration | Monochrome Multifunction Printer – Standard Copy, Print, Fax and Color Scan |
| Print Speed (Simplex) | 37 pages-per-minute |
| Print Speed (Duplex) | 10 pages-per-minute |
| Document Feeder | 80-sheets |
| Duplex Scanning | Manual duplex scanning |
| Standard Paper Capacity | 500-sheet cassette + 100-sheet multipurpose tray |
| Maximum Paper Capacity | 1,100-sheets (add (1) 500-sheet cassette) |
| Paper Weight (Cassette) | 20 – 28 lb. |
| Paper Weight (Multipurpose Tray) | 20 – 43 lb. |
| Dimensions (HxWxD) / Weight | 18.9" × 21.4" × 20.19" / 53.13 lbs. |
| Toner Yield | 24,000 based on ISO 19752 |
| Drum Yield | 60,000 |
| COPY | |
| Platen Glass | 8.5" × 14" |
| Mixed Original Support | Yes |
| First-Copy-Out-Time (Platen) | 5 seconds |
| First-Copy-Out-Time (DAADF) | 10 seconds |
| SCAN | |
| Resolution | Up to 600 × 600 dpi |
| Simplex Mono Scan Speed (300 dpi) | 25 images-per-minute |
| Simplex Color Scan Speed (300 dpi) | 8 images-per-minute |

| Scan to | PC (SMB), E-Mail, FTP, USB Flash Drive |
|--------------------------------------|---|
| Special Scan Features | E-Mail Attachment Support Outbound Scan Archiving Domain Name Shortcut Registration |
| PRINT | |
| Resolution | Up to 600 × 600 dpi |
| Secure Print | Standard |
| OS Support | Windows 2000, XP, Vista, Windows 7, Windows 8, Server 2003 & 2008; Mac OS 10.2 – 10.7; Various Linux, UNIX (Sun Solaris, AIX), SAP and AS/400 |
| Standard PDL | PCL 5e / XL |
| Optional PDL | PostScript3, Barcode, PDF |
| FAX | |
| Modem Speed / Max Compression | 33.6 Kbps / JBIG |
| Document Memory Back-Up | To memory capacity |
| Address Book | 1,000 locations |
| Group Dialing | 100 groups |
| Fax/E-Mail Mixed Transmission | Standard |
| Secure Reception | Standard |
| Inbound Fax Routing | Standard (to Fax, E-mail or PC folder) |
| Fax/E-mail Archiving | Standard (Inbound/Outbound) |
| Confirmation Report | Standard (Fax or E-Mail) |
| Special Fax Features | Delayed Transmission VoIP Support Custom Coversheet Insertion |



As an ENERGY STAR® partner, Murata Machinery, Ltd. has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Muratec and the Muratec logo are trademarks and/or registered trademarks of Murata Machinery, Ltd. or its subsidiaries in the United States and other countries. Other names, such as those of products of other companies, are the trademarks or registered trademarks of their respective companies. All specifications subject to change without notice. Not all features and options available at the time of product launch.



Muratec America, Inc.
3301 East Plano Parkway, Suite 100, Plano, TX 75074
For more information on Muratec products or services, call (469) 429-3300 or visit our web site at www.muratec.com